



By Aerovent

A GREEN INITIATIVE

# PREMIUM EFFICIENCY PRODUCTS



Aerovent is proud to present the following sizes, RPMs and voltages. See page 3 for model availability.

MOTOR DATA	HP	RPM	Voltage/ Phase	HZ	Enclosure
	1/6	1750	115/1	50/60	ODP
	1/4	1750	115/1	50/60	ODP
			208-230/1	50/60	TENV
	1/2	1750	115/1	50/60	ODP
			208-230/1	50/60	ODP
	3/4	1750	115/1	50/60	ODP
			208-230/1	50/60	ODP
	1	1160	115/1	50/60	ODP
			208-230/1	50/60	ODP
		1750	115/1	50/60	ODP
			208-230/1	50/60	ODP
			115/208-230	50/60	TEFC
	1800	460/3	50/60	OP	
	1-1/2	1800	460/3	50/60	OP
2	1750	208-230/1	50/60	TEFC	
	1800	460/3	50/60	OP	
3	1800	460/3	50/60	OP	

## Are You GridSmart™?

As the demand to reduce energy consumption continues to shape the future of the fan industry, Aerovent's new line of GridSmart™ Electronically Commutated (EC) Motors can help get you on the fast track for meeting the Department of Energy's new fan regulations. GridSmart™ EC Motors combine AC and DC voltages in order to bring our customers the best of both technologies and have the ability to maintain high efficiencies at the demanded speed of the application.

If your application requires a variable load, consider the GridSmart™ EC motors. If the flow is reduced by half, the power will be reduced by 88%!!!

## Benefits of GridSmart™ EC Motors

- Efficiencies up to 87.5%
- Constant efficiency as the motor speed is varied
- Up to 66% energy savings over traditional PSC motors
- Performance range comparable to a belt driven fan with reduced maintenance benefits of a direct drive fan
- 80% usable turndown range as compared with 40% maximum on PSC motors
- Soft start gives fans smooth, quiet start
- Lower operating temperatures result in longer life and reduces energy consumption
- Heavy-duty ball bearings are permanently lubricated



# EC MOTOR TYPES

ODP, TENV



1/6HP to 1HP  
GridSmart™ EC Motors

TEFC



1HP & 2HP  
GridSmart™ EC Motors

## Speed Control Options

- 1 Motor Mounted Dial** – Standard on EC-ODP and EC-TENV motors; Optional on EC-TEFC motors

A potentiometer is mounted to the motor housing offering full speed control range. Speed adjustment is made with a small flat head screwdriver. With this option, the motor's 0-10V DC control leads are terminated in a standard 2x4 junction box from the factory and can remain there if not required by the end user.



ODP, TENV



TEFC

- 2 0-10V DC Lead** – Standard on EC-ODP and EC-TENV motors; Optional on EC-TEFC motors

A 36" long control lead is prewired from the motor which accepts a 0-10V DC signal and can be wired into building control systems or field supplied controls. With this option, the control leads are terminated in a standard 2x4 junction box from the factory.



ODP, TENV




TEFC

- 3 Remote Mounted Dial** – Optional on EC-ODP and EC-TENV motors

A wall mounted dial allows the fan to be controlled from within the building by sending the motor a 0-10V DC option. This option includes a 115V or 230V (depending upon the motor voltage selected) to 24V AC transformer mounted in the NEMA electrical enclosure. On models ACXD, ATD/R and ATDW/R the junction box for the transformer will be located within the fan motor enclosure. On model SCDD, the junction box for the transformer will be located on the exterior of the fan.



ODP, TENV



# GRIDSMART™

EC MOTORS

By Aerovent



SCDD



ACXD



ATD | ATDR  
ATDW | ATDWR

Size	HP	Max RPM
080AE	1/6	1750
090AE	1/4	1750
100AE	1/2	1750
120AE	3/4	1750
135ANE	3/4	1750
135AE	1	1750
	2	1750
150ANE	1	1750
	2	1750
150AE	1	1160
	1	1200
	2	1750
165ANE	1	1160
	2	1750
165AE	1	1160
	2	1500

Size	HP	Max RPM
060BE	1/6	1750
070BE	1/6	1750
080BE	1/6	1750
085BE	1/6	1750
090BE	1/6	1750
095BE	1/4	1750
100BE	1/4	1750
120BE	1/2	1750
130BE	3/4	1750
140BE	3/4	1750
150BE	1	1160
	1	1400
	2	1750
160BE	1	1160
	2	1750
170BE	1	1160
	1	1000
180BE	2	1600
	1	1160
180BE	1	1160
	2	1300

Size	HP	Max RPM
073BE	1/6	1750
083BE	1/4	1750
093BE	1/4	1750
110BE	1/2	1750
120BE	3/4	1750
140BE	1	1750
	2	1750
160BE	1	1160
	1	1200
	2	1750
180BE	1	1160
	1	1100
180BE	1	1160
	2	1400